

## Street Stock – Diesel Trucks

1. Valid driver's license, vehicle registration, and vehicle insurance required.
2. Tires
  - a. Maximum diameter: 35", as read on the tire sidewall.
  - b. Must be DOT Approved, street legal tires.
3. Hitch
  - a. Stock Reese style hitch, rated class HI or higher.
  - b. Mounted in the OEM stock location
  - c. Meet height requirements defined in the General Rules.
4. Frame Height
  - a. Maximum frame height: Unlimited
  - b. Frame height is measured from the bottom of the frame, at the midpoint of the front door, to the ground.
5. Engine Modifications
  - a. Dodge (2003 and up), Ford (2003.5 and up), GM (2001 and up)
    - No engine modifications allowed.
  - b. Dodge (2002 and older), Ford (2003 and older), GM (2000 and older)
    - Limited to one fueling enhancement (chip, programmer, fueling box, or injectors).
  - c. Aftermarket air intake and filter allowed.
  - d. Aftermarket exhaust allowed.
6. Turbocharger
  - a. OEM stock turbocharger.
7. Fuel
  - b. Diesel fuel only.
  - c. No additional fuel or oxidizers, including but not limited to: Nitrous Oxide (N<sub>2</sub>O), Water-Methanol Injection (H<sub>2</sub>O — CH<sub>3</sub>OH), and Propane Injection (C<sub>3</sub>H<sub>8</sub>).
8. Weight
  - a. Maximum combined weight of vehicle and driver: 8.500 lbs.
  - b. No hanging weight(s) ahead of front bumper or after rear bumper.